

TECHNICAL DATASHEET

3544800 Clino® CR4 SC-CR Cleaning trolley for Cleanroom

Individualization
on request!

Product description

Cleaning trolley with MopScoop® CR dosing and impregnation system and disposal for non-sterile areas made of stainless steel and plastic.

- No downtime problems thanks to just-in-time impregnation
- Made from the highest quality stainless steel
- High-end surface quality through electropolishing
- Touch-free operating concept



ISO	3	4	5	6	7	8
GMP			A/B		C	D

Product specifications

Article name Article number	Clino® CR4 SC-CR 3544800
Weight	22.22 kg
Working dimension	80 x 57 x 103 cm
Resting dimension	80 x 57 x 103 cm
Basic components	Basic module (stainless steel suitable for cleanroom use) High-end finish Electrically conductive special rollers 100 mm MopScoop® dosing unit incl. plastic lid EasyMop® system box Clino® PlusBoxes Handle holder Mop frame support Unit 1 x 35 L
Work area	The cleaning trolley should be completely cleaned after use and stored in a dry place. The trolley's autoclave suitability depends on its individual components.
Disposal area	1 Pieces 1 PU
Care instructions	1 Pieces
Sterility	110 x 60 x 118 cm 22.22 kg
Pieces per PackingUnit Selling unit	2 110 x 120 x 193 cm
Pieces per box	87168000
Carton size Carton weight	Germany
Cartons per pallet Pallet	4065237106969
Customs tariff number	Our sales department will be happy to advise you on suitable accessories
Country of origin	
EAN-Number	
Compatible accessories	

Industry Sectors

Assembly Hygiene



This classification is a non-binding recommendation. The user must check the individual suitability and compatibility for his individual area of application. The condition of the material must be checked regularly; damaged products must be replaced immediately. All information without guarantee. Subject to changes and deviations.

PFENNIG Reinigungstechnik GmbH | Heubachstraße 1 | 87471 Durach | Germany
www.pfennig-reinigungstechnik.com | info@pfennig-reinigungstechnik.com | +49 (0) 831 561 22 0

Status: 30.01.2026;



3544800 Clino® CR4 SC-CR Cleaning trolley for Cleanroom

1x	3530176	Module CR4 - Facelift	Autoclavable (121 °C for 20 minutes)
1x	3530184	Insert for bag holder frame	Autoclavable (121 °C for 20 minutes)
1x	3530142	Bag support for CR1/CR4	Autoclavable (121 °C for 20 minutes)
4x	2013430	Swivel castor 100 mm	
1x	3530187	Stem for MopTen and EasyMop® system box	Autoclavable (121 °C for 20 minutes)
1x	2910000	Systembox EasyMop® blue	
1x	3500093	Holder for handle	Autoclavable (121 °C for 20 minutes)
1x	3500092	Support for Mop frames	Autoclavable (121 °C for 20 minutes)
1x	3500096	Holding frame for Clino® PlusBox	Autoclavable (121 °C for 20 minutes)
1x	3500097	Holding frame for Clino® PlusBox	Autoclavable (121 °C for 20 minutes)
1x	2088622	Clino® PlusBox blue	
1x	2088666	Clino® PlusBox grey	
2x	2088650	Transparent lid	
2x	2088653	Transparent use	
1x	2088655	Sieve transparent	
1x	3500710	MopScoop® GMP container	Autoclavable (121 °C for 20 minutes)
1x	3500721	Holding frame for MopScoop® GMP	Autoclavable (121 °C for 20 minutes)
1x	3500730	Tray for MopScoop® GMP	Autoclavable (121 °C for 20 minutes)
2x	3500735	Storage tray for MopScoop® GMP tray	
1x	3500740	Trigger for MopScoop® GMP	Autoclavable (121 °C for 20 minutes)
1x	3500750	MopScoop® GMP dosing tube	Autoclavable (121 °C for 20 minutes)
1x	3500762	Nut for MopScoop® GMP	
1x	3500753	MopScoop® GMP dosing flask 200 ml	
2x	3500755	Seal for MopScoop® GMP dosing piston	
1x	3500756	Seal for MopScoop® GMP dosing tube	
1x	3500780	Lid for MopScoop® CR	
1x	0899120	Work instruction	
1x	0899100	Cardboard small	

Diese Klassifizierung ist eine unverbindliche Empfehlung. Der Anwender muss die individuelle Eignung und Verträglichkeit für seinen individuellen Anwendungsbereich prüfen. Der Zustand des Materials ist regelmäßig zu überprüfen, beschädigte Produkte sind umgehend auszutauschen. Alle Angaben ohne Gewähr. Änderungen und Abweichungen vorbehalten.

PFENNIG Reinigungstechnik GmbH | Heubachstraße 1 | 87471 Durach | Germany
 www.pfennig-reinigungstechnik.com | info@pfennig-reinigungstechnik.com | +49 (0) 831 561 22 0

Status: 30.01.2026;

